



DELTA



MADE IN USA

DELTA JEEP® FENDER LIGHT KIT for JEEP Wrangler JK/ TJ 1997-2008 P/N 01-6550-JKB or 01-6550-TJB

INSTALLATION INSTRUCTION

1. Remove the bolt holding the lower section of the Hood Latch.
2. Insert the bolt into each Fender Light bracket.
3. Attach the Fender Light to the body of the vehicle (JK Model) or to the Fender (TJ Model).
4. Repeat this step with the other Fender Light.
5. Connect the lead wires on each Fender Light to the harness.
6. Install the relay in a close proximity to the battery.
7. Connect black wire leading from relay to metal surface under the hood with a sheet metal screw (provided).
8. Route the blue (switch wire) alongside the firewall to the driver's side and puncture through the rubber grommet to get inside the passenger compartment.
9. Install the switch on the dashboard (left to the steering column) by snapping the side panel of the dashboard and drilling ½" hole in the dashboard. For best result use our Billet Aluminum Switch Plate #05-2001-3X
10. Connect blue wire to the switch prong with lamp icon.
11. Connect the short red wire from the prong with + icon on the switch to any "hot wire" using snap-lock (provided).
12. Connect the black wire leading from the switch to any grounded metal surface under the dashboard.
13. Remove the fuse from the harness and connect the red wire leading from the relay to the positive post on the battery.
Now insert the fuse back into the fuse holder.

You may now test your lights! **HAPPY FOUR WHEELIN'**



DELTA TECH INDUSTRIES, LLC - Placentia, CA 92870, U.S.A.

Web: www.deltalights.com E-mail: sales@deltalights.com